

VERSATRAN - ISOBARIC HOSES FOR VERY HIGH PRESSURE  
 VERSATRAN - TUBI ISOBARICI YOKOHAMA PRESSIONI ELEVATE

## TUBOY28

YOKOHAMA VERSATRAN HOSE ISO18752-280 BAR  
 YOKOHAMA TUBO VERSATRAN ISO18752-280 BAR

Norme - Norma: ISO18752



### Notes

**TUBE:**  
 SYNTHETIC RUBBER, RESISTANT AGAINST  
 HYDRAULIC FLUIDS  
**REINFORCEMENT:**  
 TWO WIRE BRAID DN 06 - DN 12  
 FOUR WIRE SPIRAL DN 16 - DN 51  
 OF HIGH TENSILE STEEL WIRE  
**COVER:**  
 HIGH ABRASION AND WEATHER RESISTANT  
 SYNTHETIC RUBBER (MSHA APPROVED)  
 TEMPERATURE RANGE (FLUID):  
 FROM -40°C TO 100°C FOR BRAID HOSES  
 FROM -40°C TO 120°C FOR SPIRAL HOSES  
 DN51 NOT COMPATIBLE WITH DRYLOCK  
 RANGE FITTINGS

### Note

**SOTTOSTRATO:**  
 GOMMA SINTETICA RESISTENTE AGLI OLII  
**RINFORZO:**  
 DUE TRECCE DN 06 - DN 12  
 QUATTRO SPIRALI DN 16 - DN 51  
 DI ACCIAIO AD ALTA TENACITÀ  
**COPERTURA:**  
 GOMMA SINTETICA CON ALTA RESISTENZA  
 ALL ABRASIONE E AGLI AGENTI  
 ATMOSFERICI (OMOLOGATO MSHA)  
 RANGE DELLE TEMPERATURE (FLUIDO):  
 DA -40°C A +100°C TUBI TRECCIATI  
 DA -40°C A +120°C TUBI SPIRALATI  
 DN51 NON ASSEMBLABILE CON RACCORDI  
 GAMMA DRYLOCK

Code Article Codice Articolò	Inside ø ø Interno		ø Braid ø Treccia	ø Out ø Est	W.P. Esercizio		Burst Scoppio	Radius Raggio	Weight Peso	Ferrule Boccola
	Inch/Poll	DN (mm)	mm	mm	bar	psi	bar	mm	Kg/mt	
TUBOY0428	1/4	6	11.1	13.5	280	4000	1120	45	0.29	BUK04
TUBOY0628	3/8	10	14.3	16.9	280	4000	1120	60	0.37	BUK06
TUBOY0828	1/2	12	18.6	21.2	280	4000	1120	80	0.51	BUK08
TUBOY1028	5/8	16	24.1	26.5	280	4000	1120	140	1	BHR10
TUBOY1228	3/4	19	27.2	29.5	280	4000	1120	170	1.15	BDR12
TUBOY1628	1"	25	34.5	37	280	4000	1120	220	1.68	BDR16
TUBOY2028	1"1/4	32	42.2	45.4	280	4000	1120	460	2.54	BDR20
TUBOY2428	1"1/2	38	48.9	52.3	280	4000	1120	560	3.02	BDR24
TUBOY32SH	2"	51	63	66	280	4000	1120	630	4.65	BDR32